



TERRA FLOORING

www.terra-flooring.com

Terra Loose Lay
FAIRMONT

**BOLD.
TOUGH.
ENDURING.**

Live and thrive on luxury floors inspired by the earth.

TERRA LOOSE LAY - FAIRMONT

Colours



FMT - 501



FMT - 502



FMT - 503



FMT - 504



FMT - 505



Terra Loose Lay - the hassle-free solution that combines style, practicality, and durability, with easy installation and high-performance features.



Terra Shield

Experience a cleaner and healthier living or work space with Terra Shield's advanced antibacterial technology seamlessly integrated into the surface wear layer. Our impenetrable layer of product protection inhibits the growth and multiplication of microorganisms, providing long-term protection against odors, stains, and degradation. Terra Shield keeps your floors clean and fresh without compromising their aesthetics.



TERRA SHIELD



DiamondX

DiamondX technology harnesses the power of cultured diamonds to provide unparalleled protection against scratches, stains, and dents in LVT finishes. The secret lies in the tiny DiamondX particles embedded in the wear layer, creating a surface that's durable, clean, and resistant to heavy foot traffic. Enjoy the perfect blend of aesthetics and durability with DiamondX finish, the ultimate choice for any space.

Diamond X 
Protection



Product Structure

TERRA LOOSE LAY



Wear layer with UV coating
Fade, stain and scratch resistance, easy to clean

Vinyl layer with glass fiber
Virgin material-dent resistance, resilient

Decorative film
HD print, creative and individual design

Slip Pad
Effective anti-skid and moisture proof

Diamond X
Protection 


TERRA
FLOORING

Specifications

Terra Loose Lay

Description	Fairmont
Wear Layer Protection	Diamond X
Anti-Bacterial	Terra Shield
Total Thickness	5 mm
Wear Layer Thickness	0.55 mm
Plank Size	1219 mm x 184 mm
Emboss Type	True Random
Bevel	Micro
Installation Method	Glue Down
Packaging	10 Planks = 2.245m ² / Carton
Weight Per Sqm	9.75 kg/m ²
Warranty	15 Years Commercial, 25 Years Residential



Performance

Reaction to Fire	EN 13501-1	Bfl-S1
Slip Resistance (Dry)	EN 138393	DS
Slip Resistance (Wet)	DIN 51130	R10
Electrostatic Resistance	EN 14041	Pass
Castor Chair Resistance	ISO TR 4918	Pass
Residual Indentation	ASTM F3261-17	<0.1 mm
Dimensional Stability	ISO 23999	≤0.15%
Curling	ISO 23999	Pass
Colour Fastness to Light	ASTM F1515	Pass
Impact Sound Insulation	ASTM E492-09	IIC 56
Chemical/Stain Resistance	ASTM F925-13	Pass
Wear Resistance	EN 660-2	Class T
Indoor Air Quality VOC Test	EN ISO 10580	Exceeds Requirement
Phthalate Free	CPSC-CH-C1001-09.3	Yes
CE Marking / Classification	EN 14041:2011	Yes
Indoor AIR Quality		Floor Score



TERRA FLOORING
Live and thrive on luxury floors

Dubai Industrial City, UAE
Phone: +971 4 554 7137 | Fax: +971 4 554 7132
Email: info@terra-flooring.com | www.terra-flooring.com