

Terra Loose Lay

Description	Fairmont
Wear Layer Protection	Diamond X
Anti-Bacterial	Terra Shield
Total Thickness	5 mm
Wear Layer Thickness	0.55 mm
Plank Size	1219 mm x 184 mm
Emboss Type	True Random
Bevel	Micro
Installation Method	Glue Down
Packaging	10 Planks = 2.245m ² / Carton
Weight Per Sqm	9.75 kg/m ²
Warranty	15 Years Commercial, 25 Years Residential

Performance

Reaction to Fire	EN 13501-1	Bfl-S1
Slip Resistance (Dry)	EN 138393	DS
Slip Resistance (Wet)	DIN 51130	R10
Electrostatic Resistance	EN 14041	Pass
Castor Chair Resistance	ISO TR 4918	Pass
Residual Indentation	ASTM F3261-17	<0.1 mm
Dimensional Stability	ISO 23999	≤0.15%
Curling	ISO 23999	Pass
Colour Fastness to Light	ASTM F1515	Pass
Impact Sound Insulation	ASTM E492-09	IIC 56
Chemical/Stain Resistance	ASTM F925-13	Pass
Wear Resistance	EN 660-2	Class T
Indoor Air Quality VOC Test	EN ISO 10580	Exceeds Requirement
Phthalate Free	CPSC-CH-C1001-09.3	Yes
CE Marking / Classification	EN 14041:2011	Yes
Indoor AIR Quality		Floor Score

